Published in AJSE, Vol:21, Issue: 1 Received on 12<sup>th</sup> August 2021 Revised on 11<sup>th</sup> October 2022 Accepted on 12<sup>th</sup> October 2022

# A Cluster Based Feasible Time Interval for Tracking Lost or Stolen Vehicle

Md. Ashraful Babu, Md. Mortuza Ahmmed, Mir Kaosar Ahamed, M. Mostafizur Rahman

Abstract— The system for tracking and monitoring lost or stolen vehicle is challenging. This device is widely used to assess the vehicle's location using GPS technology. It can be used to track a vehicle or vehicle fleet and to obtain information about the vehicle's current location. There are various challenges for tracking and monitoring vehicles and finding lost vehicles due to the lack of proper real-time vehicle location and hence it is difficult to take necessary action in the immediate proper time after the vehicle has lost or stolen. In this paper a Cluster Based Feasible Time Interval for Vehicle Tracking (CFTVT) algorithm for measuring the minimum time interval for taking action after the vehicle has lost or stolen is proposed. This proposed model helps to imply any appropriate vehicle tracking algorithm in the exact proper time after the vehicle has been lost or stolen.

*Index Terms*— Lost Vehicle Tracking; Stolen Vehicle Tracking; Cluster Based Feasible Time

# I. INTRODUCTION

The system proposed in this article is to measure the minimum time interval for taking an action to find the lost or stolen vehicle. There are several systems or algorithms are available in the literature for tracking lost or stolen vehicles. But any of these systems will not be effective if it is not possible to implement in the proper time. Here, we develop a Cluster Based Feasible Time Interval for Vehicle Tracking (CFTVT) algorithm to measure the minimum time interval to implement any of the existing vehicle tracking algorithms to track the lost or stolen vehicle.

# Md. Ashraful Babu

Assistant Professor, Department of Quantitative Sciences, International University of Business Agriculture and Technology Email: <u>babu@iubat.edu</u>

# Md. Mortuza Ahmmed

Assistant Professor, Department of Mathematics, American International University - Bangladesh Email: <u>mortuza@aiub.edu</u>

# Mir Kaosar Ahamed

Assistant Professor, Department of Mathematics, Mawlana Bhashani Science and Technology University. Email: mirkaosar@mbstu.ac.bd

#### M. Mostafizur Rahman

Associate Professor, Department of Mathematics, American International University - Bangladesh Email: <u>mostafiz.math@aiub.edu</u>

The major advantages of clustering a large-scale network, where the management and the information accumulation would be attained very easily within the network clusters [1]. In order to provide an easily accessible network, clustering is done on the basis of specific application requirements. Nodes are constructed in clusters using certain parameters, such as nodes that will join the clusters, exit nodes used to leave the network. However, the clustering technique is principally handled for data distribution and routing in the network [2, 3]. Therefore, the clustering method helps to divide the whole network into several smaller sub-networks. There are many techniques found in the literature for clustering the network [4-7]. Khakpour et. al. [8] describes the main causes to use clustering in the network such as (i) aggregated network scalability by generating network fragments [9]; (ii) decreasing the quantity of communications being transferred within the network [10]; (iii) declining crowding in network communications [9,11]; (iv) serving optimum quality of service (QoS) and appropriate routing of communications [12]; (v) capturing with variable network connectivity [13]; and, (vi) shrinking argument and hidden fatal problems [14].

Several techniques for vehicle observing, vehicle alerting systems, and vehicle tracking systems have been anticipated by many researchers. Benjamin et al. [15] presented a realtime computer vision structure to trace vehicles and ensure traffic reconnaissance based on a audiovisual figure processing technique. Akande [16] offers automatic vehicle location as an innovative process to trace and scrutinize any vehicle endowed with a software unit receiving and transmitting signals over the GPS satellite. Rauf and Kamal [17] anticipated a clever GPS navigation system. In this system, a neural network is accompanied to manage impaired raw signals taken by the GPS receiver. Jianping et al. [18] developed GPS based real-time vehicle alarm monitoring and alerting system that occupied GPRS and CSD on the implanted system. Venkatakrishnan and Seethalakshmi [19] presented Public transport ticketing and monitoring system contains GPS, GSM, RFID, and Zigbee for the consumers. The usage of GSM and GPS technologies allows the system to trace vehicles and presents rationalized data about current tours. Patinge and Kolhare [20], Khan and Mishra [21], Hannan et al. [22], Pham et al. [23], Maruthi and Jayakumari [24], and many researchers developed the vehicle tracking and monitoring system for lost or stolen vehicles.

All the above-discussed systems will not be efficient if the action has not been taken at the appropriate time. In this paper, we develop such a system so that it is possible to measure the minimum time interval to take immediate necessary actions after the vehicle has been lost or stolen. The rest of the paper is divided into four sections. Section 2 described the Cluster Based Feasible Time Interval for Vehicle Tracking (CFTVT) algorithm, section 3 includes the pseudocode of the CFTVT algorithm, section 4 illustrates a numerical example implemented by the CFTVT algorithm and section 5 concludes this paper.

# II. ALGORITHM FOR VEHICLE TRACKING SYSTEM

# A. Cluster Based Feasible Time Interval for Vehicle Tracking (CFTVT) Algorithm

First, we consider a network of a city and divide this network into a number of clusters. Each of the clusters contains arcs and nodes. Some nodes connect the clusters call connecting or shared nodes and some nodes are exit nodes located on the boundary of the network.

Step-1: Identify the vehicle's last position, a node of a cluster, before the vehicle has lost or stolen;

Step-2: Find the shortest travel times from the node of the vehicle's last position to each of the exit nodes of the network.

Step-3: Find the minimum shortest travel time (say  $T_{min}^E$ ) from Step-2.

Step-4: Find the minimum shortest travel time from the vehicle's last position to any exit node through the clusters. To obtain this travel time follow the following procedure:

Find the minimum shortest travel time (say  $t_1$ ) from the vehicle's last position to among the connecting nodes of its associated clusters. Block the other associated clusters which have travel greater than  $t_1$ . Also, block the cluster where the vehicle has been lost or stolen. Again, identify the minimum shortest travel time (say  $t_2$ ) from the last connecting node to among the connecting nodes of its associated clusters. Block the other associated clusters which have travel greater than  $t_2$ .

Continue this process until no unblock cluster is available.

Step-5: Find the minimum shortest travel time (say  $t_l$ ) from the last connecting nodes found from Step-4(b) to the exit node of that cluster.

Step-6: Add all the travel time obtained from Step-4 and Step-5; say  $T_{min}^{c}$ .

Step-7: The feasible minimum time interval:  $[T_{min}^E, T_{min}^C]$ where  $T_{min}^E \leq T_{min}^C$ ; Stop.

# III. PSEUDOCODE FOR CFTVT ALGORITHM

We consider a city where the vehicle has been lost or stolen. Let G = (N, L) be the graph of the city network, where *N* be the set of nodes or vertices, and *L* be the set of links or arcs of the pairs of nodes belonging to*N*. We divide this city into a finite number of  $k (\ge 2)$  cluster network zones. Let  $C_i = (N_i, L_i) \subset G; i = 1, 2, ..., k$ ; be the *i*<sup>th</sup> cluster of the network *G*. Every two adjacent clusters have the connecting or shared node(s). Let  $a_j^{(p,q)}$  be the connecting or shared node of any two adjacent clusters  $C_p$  and  $C_q$  and let  $S = \{a_i^{(p,q)} | j \ge 1\}$  be the set of all these connecting or shared nodes. Let  $e_i^k$  be any exit node of the  $k^{th}$  cluster and let  $X = \{e_i^k | i = 1, 2, ..., m\}$  be the set of all the exit nodes. Only the clusters on the boundary of the network *G* have the exit nodes. Let  $n_i^k$  ( $i \ge 1$ ) be any node in the graph *G* located on the  $k^{th}$  cluster other than the connecting and the exit node. Let  $(i, j) \in L$  be the arc or link of any two directly connected nodes and let  $t_{ij}^k$  be the travel time from  $i^{th}$  node to  $j^{th}$  node of the  $k^{th}$  cluster.

Here we assume that the vehicle has lost or stolen on any of the nodes of any cluster. Let  $v_r^s$  of the  $r^{th}$  node located on the  $s^{th}$  cluster be the last location before the vehicle has lost or stolen. Now we apply the shortest path algorithm to find all the shortest paths from  $v_r^s$  to each of the exit nodes  $e_i^k (i = 1, 2, ..., m)$ . Let  $t_i^e (i = 1, 2, ..., m)$  be the travel times of these shortest paths. Let  $E_t = \{t_i^e | i = 1, 2, ..., m\}$  be the set of the travel times of all the shortest paths from  $v_r^s$  to each of the exit nodes  $e_i^k$ . Let  $T_{min}^E = \min\{t_i^e | t_i^e \in E_t\}$  be the minimum travel time among all the obtained shortest travel times.

Now we find the shortest path from the  $v_r^s$  node to the exit node of any boundary cluster through the associated cluster(s) of the  $s^{th}$  cluster  $C_s$ . Let  $t_1$  be the minimum travel time among the shortest path(s) from the  $v_r^s$  node of  $s^{th}$ connecting node(s)  $a_{i}^{(s,p)}; p =$ cluster to the 1, 2, ..., p, ..., q; of its associate cluster(s). Let  $C_p$  be the nearest associated cluster among all other associated clusters of the  $s^{th}$  cluster  $C_s$ . Block the other (if exists) associated cluster(s) of  $C_s$  which has the greater travel time than  $t_1$ . Again, find the shortest paths from the connecting or shared node  $a_i^{(s,p)}$  to the connecting node(s) of the associated cluster(s) of  $C_p$  and let  $t_2$  be the minimum travel time among these shortest paths. Similarly, block the other (if exists) associated cluster(s) of  $C_p$  which has the greater travel time than  $t_2$ . Continue this process until there is no unblocked associated cluster. Now find the shortest travel time, say  $t_1$ , from the connecting node of the last reached boundary cluster to the exit node of this cluster. Let  $T_{min}^{c} (= \sum_{i=1}^{l} t_i)$ be the total travel time of  $v_r^s$  node to the exit node through the associated clusters.

Therefore the time interval  $[T_{min}^E, T_{min}^C]$  where  $T_{min}^E \leq T_{min}^C$  is the feasible minimum time period for taking action to find the vehicle after lost or stolen. A formal algorithm for obtaining feasible time interval for tracking lost or stolen vehicle is given below:

Let, initially S' be the subset of S that contains the connecting or shared nodes of the associated cluster(s) of  $v_r^s$  node of the  $s^{th}$ cluster  $C_s$ .

# A. ALGORITHM CFTVT

BEGIN

Identify the vehicle's last position  $v_r^s$  node before the vehicle has lost or stolen;

Find the shortest travel times  $t_i^e$  from  $v_r^s$  node to each of the exit nodes  $e_i^k$  (i = 1, 2, ..., m):

SET 
$$T_{min}^{E} \leftarrow \min\{t_{i}^{e} | t_{i}^{e} \in E\};$$
  
SET  $p_{w}^{j} \leftarrow v_{r}^{s};$   
SET  $S' \leftarrow$   
 $\begin{cases} b_{p}^{(j,q)} | connecting node(s) of the cluster(s) \\ q associated with j^{th} cluster \\ SET T \leftarrow NULL; \end{cases} \subset S$ 

WHILE no unblocked cluster have found DO

Find the minimum travel time  $t_i$  among the shortest path(s) from  $p_w^j$  node of  $j^{th}$  cluster to all the connecting node(s) of the set S', the associated cluster(s) of  $p_w^j$  node;

 $T \leftarrow T + t_i;$ 

 $p_w^j \leftarrow b_p^q$  is the connecting node of the travel time  $t_i$ ;



Block the clusters which have the greater travel time than  $t_i$ ; ENDWHILE;

Find the shortest travel time  $t_l$ , from the connecting node to the exit node of the last reached boundary cluster;

$$I \leftarrow I + t_l;$$

SET  $T_{min}^c \leftarrow T$ ;

Feasible minimum time interval:  $[T_{min}^{E}, T_{min}^{C}]$  where  $T_{min}^{E} \leq T_{min}^{C}$ ;

END;

# IV. NUMERICAL ILLUSTRATION

Consider a city with the following network graph.



Fig 1. Graph of the Network of the City

 $A = \{0, 1, 2, 3, 4, 5\},\$ 

- $B = \{4, 5, 6, 7, 8, 9, 10\},\$
- $C = \{8, 12, 13, 18, 19, 20\},\$

$$D = \{11, 12, 16, 17, 18, 25, 26\},\$$

$$E = \{10, 14, 15, 20, 21, 22, 23, 24\}$$

The city has some Exit nodes such as  $X = \{0,9,16,24\}$  which are used to get out of this city into another city. The set of connecting or shared nodes is given by  $S = \{4,5,8,10,12,18,20\}$ . It is required to find the time interval for taking an action after any vehicle has lost or stolen in any of the nodes in this city. Let us consider the last position or node where the vehicle has lost or stolen is,  $v_r^s = 19$  in the cluster C. Here we using the Dijkstra algorithm to find the shortest path from node 19 to all of the exit nodes and shown in Table 1.

Therefore, the minimum Shortest Travel Time among all of the shortest paths is,  $T_{min}^E = 12$  along with the Shortest Path from node 19 of cluster C to node 16:  $19 \rightarrow 18 \rightarrow 17 \rightarrow 16$ .

						TA	BLE	1.							
Т	HE S	SHO	RTES	ST P	ATHS	FRO	M TH	IE NO	DDE	E OF	THI	E VE	EHI	CLE	r
		HA	VE I	LOS	T OR	STOL	LEN T	'O TH	IE E	EXIT	NO	DES	5		
	1		1	0		1	0.1				4 .				-

The shortest paths from the node of the vehicle have lost or stolen $(v_r^3)$ to the exit nodes						
Starting NodeExit Nodes $(v_r^s)$ (X)		Shortest Path (Applying Dijkstra algorithm)	Shortest Travel Time			
	0	$\begin{array}{c} 19 \rightarrow 8 \rightarrow 5 \rightarrow 2 \\ \rightarrow 0 \end{array}$	22			
	9	$19 \rightarrow 8 \rightarrow 7 \rightarrow 9$	17			
19	16	$\begin{array}{l} 19 \rightarrow 18 \rightarrow 17 \\ \rightarrow 16 \end{array}$	12			
	24	$\begin{array}{c} 19 \rightarrow 20 \rightarrow 23 \\ \rightarrow 24 \end{array}$	16			
Minimum shor	test path and	$19 \rightarrow 18 \rightarrow 17$	$T^{E}_{} = 12$			
tim	e:	$\rightarrow 16$	$I_{min} = 12$			

Now we find the shortest path from node  $v_r^s = 19$  of cluster C to the nearest exit node through the clusters. The adjacent clusters of cluster C are B, D, and E. The set of connecting nodes between cluster C and its adjacent clusters is, say,  $S_1 = \{8, 12, 18, 20\}$ . Table 2 calculates the shortest paths from node 19 to the nodes of the set  $S_1$ .

TABLE 2. THE SHORTEST PATHS FROM THE NODE  $v_r^s$  TO THE CONNECTING NODES OF THE SET  $S_1$ 

The shortest paths from the node $v_r^s$ to the connecting nodes of the set							
$S_1$							
Starting Node $(v_r^s)$	Connecting Nodes ( <b>S</b> <sub>1</sub> )	Shortest Path (Applying Dijkstra algorithm)	Shortest Travel Time				
	8	$19 \rightarrow 8$	8				
10	12	$19 \rightarrow 12$	7				
19	18	$19 \rightarrow 18$	3				
	20	$19 \rightarrow 20$	5				
Minimum sh ti	ortest path and me:	$19 \rightarrow 18$	$t_1 = 3$				
ti	me:	17 10	<b>t</b> 1 <b>5</b>				

Therefore, the nearest cluster of C is cluster D. and the minimum Shortest Travel Time from node 19 of cluster C to node 18 of cluster D is,  $t_1 = 3$ . Hence block the clusters: B, C, E.

Here, A is only the unblock adjacent cluster of the cluster D. The set of connecting nodes between cluster D and its adjacent cluster A is, say,  $S_2 = \{2\}$ . Now Table 3 demonstrate the shortest paths from node 18 of the cluster D to the nodes of the set  $S_2$ .

 TABLE 3.

 THE SHORTEST PATHS FROM NODE 18 OF THE CLUSTER D TO

 THE CONNECTING NODES OF THE SET S.

The connecting nodes of the set $3_2$							
The shortest paths from node 18 of the cluster D to the connecting							
nodes of the set $S_2$							
Starting Node	Connecting Nodes ( <b>S</b> <sub>2</sub> )	Shortest Path (Applying Dijkstra algorithm)	Shortest Travel Time				
18	2	$\begin{array}{c} 18 \rightarrow 19 \rightarrow 8 \rightarrow 5 \\ \rightarrow 2 \end{array}$	20				
Minimum sl t	hortest path and ime:	$\begin{array}{c} 18 \rightarrow 19 \rightarrow 8 \rightarrow 5 \\ \rightarrow 2 \end{array}$	$t_2 = 20$				

Thus, the nearest cluster of the cluster D is A. and the minimum Shortest Travel Time from node 18 of cluster D to node 2 of cluster A is,  $t_2 = 20$ . There is no unblocked adjacent cluster left for cluster A and the exit node of cluster A is 0.

TABLE 4.								
THE SHORTEST PATHS FROM NODE 2 OF CLUSTER A TO THE								
EXIT NODE 0								
The shortest paths from node 18 of the cluster D to the connecting								
nodes of the set $S_2$								
Starting Node	Exit Nodes (X)	Shortest Path (Applying Dijkstra algorithm)	Shortest Travel Time					
2	0	$2 \rightarrow 0$	5					
Minimum sho tir	ortest path and ne:	2  ightarrow 0	$t_3 = 5$					

Here, Table 4 shows the shortest path from node 2 to the exit node 0 of this cluster A is  $t_3 = 5$ . Hence block cluster A. Thus, the minimum Shortest Travel Time from the node

of the vehicle has lost or stolen  $v_r^s = 19$  to the nearest exit node through the clusters is,

 $T_{min}^{c} = t_1 + t_2 + t_3 = 3 + 20 + 5 = 28.$ 

Therefore, the expected minimum travel time interval for taking action after the vehicle has stolen is  $[T_{min}^{E}, T_{min}^{C}] = [12, 28].$ 

#### V. CONCLUSION

In this paper, we developed an algorithm to measure the minimum time interval to take necessary action after any vehicle has been lost or stolen. Many algorithms and systems have been found in the literature for tracking lost or stolen vehicles, but these algorithms cannot possibly imply if the action has not been taken at the appropriate time. Our developed model is easy to implement and is adaptable to any existing vehicle tracking algorithm. Further research can be conducted to integrate the CFTVT algorithm along with the existing vehicle tracking algorithm.

#### REFERENCES

- P. Basu, N. Khan, T. Little, A mobility based metric for clustering in mobile ad hoc networks, in: Distributed Computing Systems Workshop, 2001 International Conference on, 2001, pp. 413–418. doi:10.1109/CDCS.2001.918738.
- [2] G. Maia, L. Villas, A. Boukerche, A. Viana, A. Aquino, A. Loureiro, Data dissemination in urban vehicular ad hoc networks with diverse traffic conditions, in: Computers and Communications (ISCC), 2013 IEEE Symposium on, 2013, pp. 000459–000464. doi:10.1109/ISCC.2013.6754989.
- [3] T. Wang, G. Wang, Tibcrph: Traffic infrastructure based cluster routing protocol with handoff in vanet, in: Wireless and Optical Communications Conference (WOCC), 2010 19th Annual, 2010, pp.1–5. doi:10.1109/WOCC.2010.5510626.
- [4] L. Maglaras, D. Katsaros, Distributed clustering in vehicular networks, in: Wireless and Mobile Computing, Networking and Communications (WiMob), 2012 IEEE 8th International Conference on, 2012, pp. 593–599. doi:10.1109/WiMOB.2012.6379136.
- [5] A. Ahizoune, A. Hafid, A new stability based clustering algorithm (sbca) for vanets, in: Local Computer Networks Workshops (LCN Workshops), 2012 IEEE 37th Conference on, 2012, pp. 843–847. doi: 10.1109/LCNW.2012.6424072.
- [6] Z. Zhang, A. Boukerche, R. Pazzi, A novel multi-hop clustering scheme for vehicular ad-hoc networks, in: Proceedings of the 9th ACM International Symposium on Mobility Management and Wireless Access, MobiWac '11, ACM, New York, NY, USA, 2011, pp. 19–26. doi:10.1145/2069131.2069135.
- [7] H. Su, X. Zhang, Clustering-based multichannel mac protocols for qos provisionings over vehicular ad hoc networks, Vehicular Technology, IEEE Transactions on 56 (6) (2007) 3309–3323. doi:10.1109/TVT.2007.907233.
- [8] S. Khakpour et al., Using Clustering for Target Tracking in Vehicular Ad Hoc Networks, Veh. Commun. (2017), http://dx.doi.org/10.1016/j.vehcom.2017.02.002
- [9] W. Fan, Y. Shi, S. Chen, L. Zou, A mobility metrics based dynamic clustering algorithm for vanets, in: Communication Technology and Application (ICCTA 2011), IET International Conference on, 2011, pp. 752– 756. doi:10.1049/cp.2011.0769.

- [10] L. Maglaras, D. Katsaros, Distributed clustering in vehicular networks, in: Wireless and Mobile Computing, Networking and Communications (WiMob), 2012 IEEE 8th International Conference on, 2012, pp. 593–599. doi:10.1109/WiMOB.2012.6379136.
- [11] A. Tizghadam, A. Leon-Garcia, Autonomic traffic engineering for network robustness, Selected Areas in Communications, IEEE Journal on 28 (1) (2010) 39–50. doi:10.1109/JSAC.2010.100105.
- [12] Z. Rawshdeh, S. Mahmud, Toward strongly connected clustering structure in vehicular ad hoc networks, in: Vehicular Technology Conference Fall (VTC 2009-Fall), 2009 IEEE 70th, 2009, pp. 1–5. doi:10.1109/VETECF.2009.5378799.
- [13] K. Hafeez, L. Zhao, Z. Liao, B.-W. Ma, A fuzzy-logicbased cluster head selection algorithm in vanets, in: Communications (ICC), 2012 IEEE International Conference on, 2012, pp. 203–207. doi:10.1109/ ICC.2012.6363839.
- [14] C. Shea, B. Hassanabadi, S. Valaee, Mobility-based clustering in vanets using affinity propagation, in: Global Telecommunications Conference, 2009. GLOBECOM 2009. IEEE, 2009, pp. 1–6. doi:10.1109/GLOCOM.2009.5425236.
- [15] Benjamin Coifman, David Beymer, Philip McLauchlan, Jitendra Malik, "A real-time computer vision system for vehicle tracking and traffic surveillance," Transportation research part C6, 1998.
- [16] Akande Noah Oluwatobi, "A GPS based automatic vehicle location system for bus transit," 1999.
- [17] Muhammad Rauf, Ahmed N. Abdalla, Nik M. Kamal, Azher Fakhruddin, "Design of intelligent GPS system navigation for bus monitoring and station reporting," National Conference on Postgraduate Research (NCONPGR), 2009.
- [18] Xing Jianping, Zhang jun, Cheng Hebin, Li Changging, Shi xiaohui, "GPS real time vehicle alarm monitoring system base on GPRS and CSD using the embedded system," International Conference on ITS Telecommunications, 2006.
- [19] V. Venkatakrishnan, R. Seethalakshmi, "Public transport ticketing and monitoring system," Journal of Theoretical and Applied Information Technology, Vol. 38, No.1, April 2012.
- [20] Prafill D. Patinge, N. R. Kolhare, "Smart onboard public information system using GPS and GSM integration for public transport," International Journal of Advanced Research in Computer and Communication Engineering, Vol. 1, Issue V, July 2012.
- [21] Abid Khan, Ravi Mishra, "GPS-GSM based tracking system," International Journal of Engineering Trends and Technology, Vol. 3, Issue 2, pp: 161-164, 2012.
- [22] M. A. Hannan, A. M. Mustapha, A. Hussain, H. Basri, " Intelligent bus monitoring and management system," Proceeding of the World Congress on Engineering and Computer Science, Vol. II, October 24-26, 2012.
- [23] Hoang Dat Pham, M. Drieberg, Chi Cuong Nquyen, "Development of vehicle tracking system using GPS and GSM modem," IEEE Conference on Open System, pp: 89-94, 2013.
- [24]R. Maruthi, C. Jayakumari, "SMS based bus tracking system using open source technologies," International Journal of Computer Application, Volume 86, No 9, January 2014.



**Dr. Md. Ashraful Babu** is an Assistant Professor of the Department of Quantitative Sciences at the International University of Business Agriculture and Technology, Bangladesh. Dr. Babu had been awarded the degrees of Ph.D. (2019) in Mathematics from the Department of Mathematics, Jahangirnagar University, Bangladesh. He had been trained professionally in Programming languages (C, C++, Fortran, R, PYTHON, PHP), Database (SQL), Optimization Software (CPLEX, TORA, LINGO, WinQSB), Data Analysis (SPSS, Eviews,) and Graphic Design. His research interests lie in Optimization and Operations Research, especially on Transportation Problem.



Md. Mortuza Ahmmed did his B.Sc. and M.Sc. in Statistics, Biostatistics and Informatics from University of Dhaka in 2007 and 2009 respectively. He is currently working as an Assistant Professor in Statistics under Department of Mathematics, American International University – Bangladesh. His research interests include demography,

education, epidemiology etc. He has published several articles in local and international peer reviewed journals and conferences.



Mir Kaosar Ahamed is an Assistant Professor in the Department of Mathematics, Mawlana Bhashani Science and Technology University, Tangail, Bangladesh. He moreover served as a Senior Lecturer in Mathematics at Daffodil International University, Dhaka, Bangladesh. Mr. Mir Ahamed attained B.Sc. Honors

(2013) and M.S. (2014) in Mathematics from Jahangirnagar University, Bangladesh. He had been prepared professionally in Programming languages (FORTRAN, Mathematica 5.0, Mathlab, C, C++, and HTML) Data analysis (SPSS). His research interests lie in Operations management, particularly on Facility Layout Planning. Much of his work has been on layout design with the help of fuzzification process. A few of his work has been on Forecasting and Statistical analysis. Mir Ahamed published several research articles in different national and international journals.



**Dr. M. Mostafizur Rahman** is basically a mathematician with extensive experience of mathematical modeling in multi-disciplinary environment. Dr. M. Mostafizur Rahman was born and brought up in Dhaka, Bangladesh. He completed his bachelor in mathematics and masters in applied mathematics from the University of Dhaka. He holds a PhD

in information engineering from the University of Padova, Italy and worked as a post-doctoral research fellow for two years in the same University. He is serving as an Associate Professor in the department of Mathematics at American International University-Bangladesh.